


## Roulement conique 1380-1329-JTEKT - 1380-1329-KOYO

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/1380-1329-koyo>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_{\text{max}}$	$r_{\text{min}}$	$C_r$	$C_{10}$	Grease lub.	Oil lub.
22.225	53.975	19.368	20.168	14.288	1.6	1.6	36.7	37.9	8 000	11 000

Bearing No.		Load center (mm) $a$	Mounting dimensions (mm)						Constant $e$	Axial load factors		(Refer to)	
Inner ring	Outer ring		$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.		$Y_1$	$Y_2$	Inner ring	Outer ring
1380	1329	11.6	29.5	29.5	46.0	49.0	1.6	1.6	0.29	2.05	1.13	0.137	0.082

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952425467
Diam. intérieur	22.225 mm
Diam. extérieur	53.388 mm
Épaisseur	19.368 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE