


Roulement conique 28158-28300-JTEKT - 28158-28300-KOYO

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/28158-28300-koyo>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
40.000	76.200	20.638	20.940	15.507	1.6	1.2	57.3	65.9	5 300	7 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
28158	28300	16.5	47.5	45.0	68.0	71.0	1.6	1.2	0.40	1.49	0.82	0.266	0.137

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250107252
Diam. intérieur	40 mm
Diam. extérieur	76.2 mm
Épaisseur	20.638 mm
Poids	412 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE