


## Galet de came avec axe CF16-VUUR-IKO - CF16-VUUR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cf16-vuur-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



CF-VUUR

| Stud dia.<br>mm        | Identification number   |                  |                             |                |                         |                |                             |                | Mass (Ref.)                    |                           |                                       |   |  |        |
|------------------------|-------------------------|------------------|-----------------------------|----------------|-------------------------|----------------|-----------------------------|----------------|--------------------------------|---------------------------|---------------------------------------|---|--|--------|
|                        | Shield type             |                  |                             |                | Sealed type             |                |                             |                | g                              | D                         | C                                     | d <sub>1</sub>                                    |  |        |
|                        | With crowned outer ring |                  | With cylindrical outer ring |                | With crowned outer ring |                | With cylindrical outer ring |                |                                |                           |                                       |   |  |        |
| 16                     | CF 16 VUUR              |                  |                             |                |                         |                |                             |                | 173                            | 35                        | 18                                    | 16  |  |        |
| Boundary dimensions mm |                         |                  |                             |                |                         |                |                             |                |                                |                           |                                       |   |  |        |
| G                      | G <sub>1</sub>          | B <sub>max</sub> | B <sub>1max</sub>           | B <sub>2</sub> | B <sub>3</sub>          | C <sub>1</sub> | g <sub>1</sub>              | g <sub>2</sub> | f <sup>(1)</sup><br>Min.<br>mm | Mounting<br>torque<br>N·m | Ball dynamic<br>load rating<br>C<br>N | Ball static<br>load rating<br>C <sub>0</sub><br>N | Maximum<br>allowable<br>static load<br>N |        |
| M16×1.5                | 17                      | 19.6             | 52.1                        | 32.5           | 8                       | 0.8            | 6                           | 3              | 0.6                            | 26                        | 58.5                                  | 20 700  | 37 600                                   | 23 200 |

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3616060458568 |
| Diam. intérieur | 16 mm         |
| Diam. extérieur | 35 mm         |
| Épaisseur       | 18 mm         |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE