

Galet de came avec axe CF8-UURM-IKO - CF8-UURM-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cf8-uurm-iko>

IKO
CAM FOLLOWERS
Standard Type Cam Followers With Cage/With Screwdriver Slot

CF-UUR

| Stud dia. mm | Identification number | | | | Mass (Ref.) | | | | |
|-----------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|-------|
| | Shield type | | Sealed type | | g | D | C | d ₁ | G |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | |
| 8 | | | CF 8 | UURM | 28.5 | 19 | 11 | 8 | M 8×1 |

| Boundary dimensions mm | | | | | | | | | | Mounting dimension f Min. mm | Maximum tightening torque N·m | Ball diameter load rating C | Ball static load rating C ₀ | Maximum allowable static load N |
|------------------------|---------|----------------|----------------|----------------|----------------|----------------|----------------|--------------------|-----|---------------------------------------|--|-----------------------------------|--|--|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | r _s max | (°) | | | | | |
| 10 | 12.2max | 32.2max | 20 | — | 0.6 | *4 | — | 0.3 | 13 | 7.1 | 4 250 | 4 740 | 4 620 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952441054 |
| Diam. intérieur | 8 mm |
| Diam. extérieur | 19 mm |
| Epaisseur | 11 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE