


Galet de came avec axe CF12-IKO - CF12-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cf12-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF

| Stud dia. mm | Identification number | | | | Mass (Ref.) | | | | |
|-----------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|---------|
| | Shield type | | Sealed type | | g | D | C | d ₁ | G |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | |
| 12 | CF 12 | | | | 95 | 30 | 14 | 12 | M12×1.5 |

| Boundary dimensions mm | | | | | | | | | | | | | |
|------------------------|---------|----------------|----------------|----------------|----------------|----------------|----------------|---------------------------|-----------------|---------------------------------------|----------------------------------|--|--|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | r _s max (°) | f Min. mm | Maximum ignoring stress N·mm | Ball dynamic load rating C | Ball static load rating C ₀ | Maximum allowable static load N |
| 13 | 15.2max | 40.2max | 25 | 6 | 0.6 | 6 | 3 | 0.6 | 21 | 21.9 | 7 910 | 9 790 | 9 790 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952441252 |
| Diam. intérieur | 12 mm |
| Diam. extérieur | 30 mm |
| Epaisseur | 14 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE