


## Galet de came avec axe CF30-R-IKO - CF30-R-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cf30-r-iko>



### CAM FOLLOWERS

Standard Type Cam Follower With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d <sub>1</sub>	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30	CF30	R			1 870	80	35	30	M30×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum ignoring torque N·m	Ball dynamic load rating C N	Ball static load rating C <sub>0</sub> N	Maximum allowable static load N	
G <sub>1</sub>	B	B <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	G <sub>1</sub>	G <sub>2</sub>	r <sub>max</sub>	(°)						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952441566
Diam. intérieur	30 mm
Diam. extérieur	80 mm
Epaisseur	35 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE