

Galet de came avec axe CFE20-UUR-IKO - CFE20-UUR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cfe20-uur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller, mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		\emptyset	D	C	d_2						
27	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	500	52	24	27						
CFE 20 UUR														
Boundary dimensions, mm														
G	B ₃	B _{max}	B ₁ max	B ₂	C ₁	g ₁	G ₁	(1) r _{max}	Mounting dimension f	Maximum tightening torque	Basic dynamic load rating C	Basic static load rating C ₀	Maximum allowable axial load	
M20 X 1.5	19.5	25.6	66.1	40.5	0.8	8	21	1	0.8	34	119	20 700	34 600	34 600

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060460059
Diam. intérieur	27 mm
Diam. extérieur	52 mm
Épaisseur	24 mm
Poids	500 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE