

Galet de came avec axe CFE24-1-UUR-IKO - CFE24-1-UUR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cfe24-1-uur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller, mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		\emptyset	D	C	d_2
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33	CFE 24-1 UUR				1 220	72	29	33

Boundary dimensions, mm										Eccentricity e	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	g ₁	G ₁	(¹) r _{max}	r						
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	30 500	52 600	52 000	

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060460165
Diam. intérieur	33 mm
Diam. extérieur	72 mm
Épaisseur	29 mm
Poids	1220 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE