

Galet de came avec axe CFE30-V-IKO - CFE30-V-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cfe30-v-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric axle mm	Identification number				Mass (Ref.) g	D	C	d _a
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE 30 V				2 030	80	35	41

Boundary dimensions mm										Eccentricity E	Mounting diameter f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₂ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	r ₁ max						
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	67 700	144 000	85 900	

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060461315
Diam. intérieur	41 mm
Diam. extérieur	80 mm
Épaisseur	35 mm
Poids	2030 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE