

Galet de came avec axe CFE30-2-V-IKO - CFE30-2-V-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cfe30-2-v-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric axle mm	Identification number				Mass (Ref.) g	D	C	d _a
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE30-2-V				2 380	90	35	41

Boundary dimensions mm										
G	B ₃	B _{max}	B ₁ _{max}	B ₂	C ₁	g ₁	G ₁	r ₁ _{max} (°)	Eccentricity E	Mounting clearance f Min. mm
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49
										Maximum operating torque N·m
										438
										Basic dynamic load rating C
										67 700
										Basic static load rating C ₀
										144 000
										Maximum allowable static load
										85 900

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060461391
Diam. intérieur	41 mm
Diam. extérieur	90 mm
Épaisseur	35 mm
Poids	2380 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE