

## Galet de came avec axe CR20-BR-IKO - CR20-BR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr20-br-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers With Cage/With Hexagon Hole

CR20-BR

Stud dia. mm (inch)	Identification number				Mass (Ref.)	g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
<b>12.700</b> ( $\frac{1}{2}$ )	<b>CR 20</b>	<b>BR</b>			132	31.750 ( $\frac{1}{2}$ )	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	J <sub>1</sub> -20	15.875 ( $\frac{5}{8}$ )	
Boundary dimensions mm/inch											
B	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	E <sub>1</sub>	E <sub>2</sub>	H	r	Bearing dimension f mm/ mm(inch)	Maximum spinning torque C N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
20.410	31.750 ( $\frac{1}{2}$ )	7.838 ( $\frac{5}{16}$ )	0.794 ( $\frac{1}{16}$ )	4.782 ( $\frac{3}{8}$ )	3.175 ( $\frac{1}{4}$ )	6.350 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{8}$ )	21.828 ( $\frac{7}{8}$ )	27.7	14 200	16 000

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462534
Diam. intérieur	12.7 mm
Diam. extérieur	31.75 mm
Épaisseur	19.05 mm
Poids	132 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE