


Galet de came avec axe CR24-B-IKO - CR24-B-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr24-b-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole



CR-B

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
15.875 ($\frac{5}{8}$)	CR 24 B				225	38.100 ($1\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	F ₁ -18	19.050 ($\frac{3}{4}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f mm/inch	Maximum ignoring torque C N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N
23.8 (0.93)	38.100 ($1\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.702 ($\frac{3}{16}$)	3.969 ($\frac{1}{8}$)	7.938 ($\frac{3}{8}$)	1.588 ($\frac{1}{16}$)	25.196 ($1\frac{1}{8}$)	55.7	19 600	24 300

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952460314
Diam. intérieur	15.875 mm
Diam. extérieur	38.1 mm
Épaisseur	22.225 mm
Poids	225 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE