

Galet de came avec axe CR32-BR-IKO - CR32-BR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr32-br-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole

CR32-BR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
22.225 ($\frac{7}{8}$)	CR 32	BR			615	50.800 (2)	31.750 (1 $\frac{1}{4}$)	22.225 ($\frac{7}{8}$)	$\frac{1}{4}$ -14	25.400 (1)	
Boundary dimensions mm/inch											
B max	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm/inch	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
33.5 (1.32)	50.800 (2)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	11.112 ($\frac{7}{16}$)	1.588 ($\frac{1}{16}$)	37.306 (1 $\frac{3}{16}$)	162	32 500	63 900

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462701
Diam. intérieur	22.225 mm
Diam. intérieur	7/8" inch
Diam. extérieur	50.8 mm
Diam. extérieur	2" inch
Epaisseur	31.75 mm
Epaisseur	1 1/4" inch
Poids	615 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE