


Galet de came avec axe CR36-B-IKO - CR36-B-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr36-b-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
22.225 ($\frac{7}{8}$)	CR 36 B				750	57.150 ($2\frac{1}{4}$)	31.750 ($1\frac{1}{4}$)	22.225 ($\frac{7}{8}$)	$\frac{1}{4}$ -14	25.400 (1)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum ignoring torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
33.5 (1.32)	58.800 (2.3)	12.700 ($\frac{1}{2}$)	6.794 ($\frac{1}{4}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	11.112 ($\frac{7}{8}$)	1.588 ($\frac{1}{16}$)	37.306 ($1\frac{3}{8}$)	162	32 500	63 900

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462725
Diam. intérieur	22.225 mm
Diam. extérieur	57.15 mm
Épaisseur	31.75 mm
Poids	750 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE