

Galet de came avec axe CR14-UU-IKO - CR14-UU-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr14-uu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
9.525 ($\frac{3}{8}$)			CR 14 UU	46	22.225 ($\frac{7}{8}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{3}{8}$)	
Boundary dimensions (mm/inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm/inch	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
14.2 9.52	22.225 ($\frac{7}{8}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	2.381 ($\frac{3}{32}$)	0.794 ($\frac{1}{32}$)	15.081 ($\frac{5}{8}$)	10.8	4.730	9.810

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462893
Diam. intérieur	9.525 mm
Diam. extérieur	22.225 mm
Epaisseur	12.7 mm
Poids	46 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE