

## Galet de came avec axe CR16-IKO - CR16-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr16-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
11.112 ( <sup>7</sup> / <sub>16</sub> )		<b>CR 16</b>			73	25.400 (1)	15.875 (5/8)	11.112 (7/16)	5-20	12.700 (1/2)
Boundary dimensions (mm/inch)										
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	δ <sub>1</sub>	δ <sub>2</sub>	r	Mounting dimension f Min. mm/inch	Maximum tightening torque C	Basic dynamic load rating C <sub>0</sub>	Basic static load rating C <sub>0</sub>
17.3 (2/3)	25.400 (1)	6.350 (1/4)	0.794 (1/32)	4.762 (3/16)	3.175 (1/8)	1.191 (1/8)	17.859 (5/8)	17.4	8.910	10.800

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462916
Diam. intérieur	11.112 mm
Diam. intérieur	7/16" inch
Diam. extérieur	25.4 mm
Diam. extérieur	1" inch
Epaisseur	15.875 mm
Epaisseur	5/8" inch
Poids	73 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE