

Galet de came avec axe CR26-IKO - CR26-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr26-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
15.875 (5/8)		CR 26			260	41.275 (1 1/2)	22.225 (7/8)	15.875 (5/8)	J ₁ -18	19.050 (3/4)
Boundary dimensions (mm/inch)										
B max	B ₂	B ₃	C ₁	δ ₁	δ ₂	r	Mounting dimension f Min. mm/inch	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
23.8 (9/16)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/16)	4.762 (3/16)	3.969 (1/8)	1.588 (1/16)	26.199 (1 1/16)	55.7	19 800	24 300

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463005
Diam. intérieur	15.875 mm
Diam. intérieur	5/8" inch
Diam. extérieur	41.275 mm
Diam. extérieur	1 5/8" inch
Epaisseur	22.225 mm
Epaisseur	7/8" inch
Poids	260 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE