

Galet de came avec axe CR32-R-IKO - CR32-R-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr32-r-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Screwdriver Slot

CR32-R

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
22.225 ($\frac{7}{8}$)	CR 32 R				615	50.800 ($\frac{2}{1}$)	31.750 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	$\frac{1}{4}$ -14	25.400 ($\frac{1}{1}$)
Boundary dimensions (mm/inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	F	Bearing dimension f Min. mm/inch	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
33.5-132	50.800 ($\frac{2}{1}$)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	1.588 ($\frac{1}{16}$)	37.506 ($\frac{1}{2}$)	192	32 500	69 900

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463036
Diam. intérieur	22.225 mm
Diam. extérieur	50.8 mm
Epaisseur	31.75 mm
Poids	615 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE