

Galet de came avec axe CR36-UUR-IKO - CR36-UUR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr36-uur-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR- UUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
22.225 ($\frac{7}{8}$)			CR 36	UUR	750	57.150 ($2\frac{1}{4}$)	21.750 ($1\frac{1}{4}$)	22.225 ($\frac{7}{8}$)	7-14	25.400 (1)
Boundary dimensions (mm/inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm/inch	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
33.5-132	50.800 (2)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{8}$)	4.762 ($\frac{3}{8}$)	4.762 ($\frac{3}{8}$)	1.588 ($\frac{1}{8}$)	27.306 ($1\frac{1}{8}$)	192	32 500	69 900

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463050
Diam. intérieur	22.225 mm
Diam. extérieur	57.15 mm
Epaisseur	31.75 mm
Poids	750 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE