


Galet de came avec axe CR16-V-IKO - CR16-V-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr16-v-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR-V

Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type With cover With cylindrical outer ring		Sealed type With cover With cylindrical outer ring		ϕ	D	C	d_1	G UNF	G_1
11.112 ($\frac{7}{16}$)	CR 16 / V				74	25.400 (1)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{3}{8}$ -20	12.700 ($\frac{1}{2}$)
Boundary dimensions: mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque C N-m	Basic dynamic load rating C N	Basic static load rating C_0 N		
B max	B_2	B_3	C_1	g_1					g_2	r
17.3.0.88	25.400 (1)	8.350 ($\frac{1}{3}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	1.191 ($\frac{1}{16}$)	17.668 ($\frac{3}{4}$)	17.4	13 100	22 700

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463555
Diam. intérieur	11.112 mm
Diam. extérieur	25.4 mm
Epaisseur	15.875 mm
Poids	74 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE