

## Galet de came avec axe CR16-VBR-IKO - CR16-VBR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr16-vbr-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

Stud dia. mm (inch)	Identification number				Mass (Ref.)		$d_1$	G	G <sub>1</sub>		
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Sealed type With cover outer ring	Sealed type With cylindrical outer ring	g	D					
11.112 ( $\frac{7}{16}$ )	<b>CR 16</b>	<b>VBR</b>			74	25.400 ( $\frac{1}{1}$ )	15.875 ( $\frac{3}{4}$ )	11.112 ( $\frac{7}{16}$ )	$\frac{3}{8}$ -20	12.700 ( $\frac{1}{2}$ )	
Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	H					r
17.3 (0.68)	25.400 ( $\frac{1}{1}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	3.175 ( $\frac{1}{8}$ )	6.350 ( $\frac{1}{4}$ )	1.191 ( $\frac{1}{8}$ )	17.859 ( $\frac{3}{4}$ )	17.4	13 100	22 700

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463586
Diam. intérieur	11.112 mm
Diam. extérieur	25.4 mm
Epaisseur	15.875 mm
Poids	74 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE