

Galet de came avec axe CR16-VBUUR-IKO - CR16-VBUUR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr16-vbuur-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR16-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Sealed type With cover outer ring	Sealed type With cylindrical outer ring							
11.112 ($\frac{7}{16}$)			CR 16 VBUUR		74	25.400 ($\frac{1}{1}$)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{1}{2}$ -20	12.700 ($\frac{1}{2}$)	
Boundary dimensions mm(inch)								Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H	r				
17.3 (0.68)	25.400 ($\frac{1}{1}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{16}$)	4.782 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	6.350 ($\frac{1}{4}$)	1.191 ($\frac{1}{8}$)	17.859 ($\frac{7}{8}$)	17.4	13 100	22 700

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060463609
Diam. intérieur	11.112 mm
Diam. extérieur	25.4 mm
Epaisseur	15.875 mm
Poids	74 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE