


Galet de came avec axe CR26-VBUU-IKO - CR26-VBUU-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr26-vbuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR--VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cover outer ring	Shield type With cylindrical outer ring							
15.875 ($\frac{5}{8}$)			CR 26	VBUU	265	41.275 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{4}$ -18	19.050 ($\frac{3}{4}$)	
Boundary dimensions mm(inch)											
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H	r	Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
23.8 (0.93)	38.100 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	3.969 ($\frac{1}{8}$)	7.938 ($\frac{1}{4}$)	1.588 ($\frac{1}{16}$)	26.195 ($\frac{1}{2}$)	55.7	29 200	40 100

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060464019
Diam. intérieur	15.875 mm
Diam. extérieur	41.275 mm
Epaisseur	22.225 mm
Poids	265 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE