

Galet de came avec axe CR32-VBUUR-IKO - CR32-VBUUR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr32-vbuur-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

CR32-VBUUR

| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G UNF | G ₁ | |
|-------------------------------|---|---|---|---|--------------------------|---|--|--|--|----------------|--------|
| | Shield type With cover outer ring | Shield type With cylindrical outer ring | Sealed type With cover outer ring | Sealed type With cylindrical outer ring | | | | | | | |
| 22.225 ($\frac{7}{8}$) | | | CR 32 | VBUUR | 627 | 50.800 (2) | 31.750 (1) ($\frac{5}{8}$) | 22.225 ($\frac{7}{8}$) | $\frac{1}{4}$ -14 | 25.400 (1) | |
| Boundary dimensions mm (inch) | | | | | | Mounting dimension f Min. mm (inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | | |
| B max | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | | | | | H | r |
| 33.5 (1.32) | 50.800 (2) | 12.700 ($\frac{1}{2}$) | 0.794 ($\frac{1}{32}$) | 4.762 ($\frac{3}{16}$) | 4.762 ($\frac{3}{16}$) | 11.112 ($\frac{7}{16}$) | 1.588 ($\frac{1}{16}$) | 37.365 (1) ($\frac{3}{4}$) | 162 | 45 700 | 80 600 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060464231 |
| Diam. intérieur | 22.225 mm |
| Diam. extérieur | 50.8 mm |
| Epaisseur | 31.75 mm |
| Poids | 627 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE