

## Galet de came avec axe CR36-VBR-IKO - CR36-VBR-IKO

<https://www.123roulement.com/roulement-palier/roulement-bille/galet-came-axe/cr36-vbr-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers With Cage/With Screwdriver Slot

Stud dia. mm (inch)	Identification number		Shield type With cover With cylindrical outer ring	Sealed type With cylindrical outer ring	Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	CR 36	VBR									
22.225 ( $\frac{7}{8}$ )	CR 36	VBR			759	57.150 (2 $\frac{1}{2}$ )	31.750 (1 $\frac{1}{2}$ )	22.225 (7/8)	7/14	25.400 (1)	
Boundary dimensions mm (inch)						Mounting dimension f Min. mm (inch)	Maximum spinning torque N·m	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
33.5 (1.32)	50.800 (2)	12.700 (1/2)	0.794 ( $\frac{1}{4}$ )	4.762 ( $\frac{3}{8}$ )	4.762 ( $\frac{3}{8}$ )	11.112 ( $\frac{7}{8}$ )	1.588 ( $\frac{1}{8}$ )	37.305 (1 $\frac{3}{8}$ )	162	45 700	80 600

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060464293
Diam. intérieur	22.225 mm
Diam. extérieur	57.15 mm
Épaisseur	31.75 mm
Poids	759 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE