


Roulement à aiguilles NQ20-20-JTEKT - NQ20-20-KOYO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nq20-20-koyo>

Machined ring needle roller bearings ————— **Koyo**

F_w 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
20	—	28	20	—	14.4	23.0	23 000	NQ20/20
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
d_a	D_a	r_a		0.038	—			
max.	max.	max.						
—	26	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477435
Diam. intérieur	20 mm
Diam. extérieur	28 mm
Épaisseur	20 mm
Poids	38 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE