

Rotule SA SAL8-T-K-DURBAL - DSAL8-T-K-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/dsal8-t-k-durbal>


SAL8-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
SAL 8 T/K		8	M 8	12	9,00	24	
type	l ₁ min	measurement [mm]		h	alpha [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
SA / SAL 8 T/K	25			42	14	12,9	0,038

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490007
Diam. intérieur	8 mm
Diam. extérieur	24 mm
Epaisseur	12 mm
Type	-
Poids	38 g
Filetage	-
Lubrification	-
Conditionnement	-
Norme	-

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE