

Rotule SA


SAL16-T-K-DURBAL - SAL16-T-K-DURBAL

https://www.123roulement.com/roulement-palier/rotule/sa/sal16-t-k-durbal


SAL16-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| SAL 16 T/K | | 16 | M 16 | 21 | 15,00 | 42 |

| type | measurement [mm] | | h | α [°] | Tragzahlen C ₁₀ [kN] | weight [kg] |
|-----------------|--------------------|----------------|----|-------|---------------------------------|-------------|
| | l ₁ min | l ₂ | | | | |
| SA / SAL 16 T/K | 37 | 21 | 66 | 15 | 39,0 | 0,210 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952490168 |
| Diam. intérieur | 16 mm |
| Diam. extérieur | 42 mm |
| Epaisseur | 21 mm |
| Type | SA |
| Poids | 210 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE