

Rotule SA SSA25-T-K-DURBAL - SSA25-T-K-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/ssa25-t-k-durbal>

SSA25-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
SSA 25 T/K	25		G	B	C1	d2	
			M 24 x 2	31	22,00	60	

type	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
	l1 min	l2 min	h			
SSA / SSAL 25 T/K	55	30	94	15	85,0	0,640

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490946
Diam. intérieur	25 mm
Diam. extérieur	60 mm
Epaisseur	31 mm
Type	SA
Poids	640 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE