

Rotule SA SSAL25-T-K-DURBAL - SSAL25-T-K-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/ssal25-t-k-durbal>

SSAL25-T-K



male thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2
SSAL 25 T/K			25	M 24 x 2	31	22,00	60

type	measurement [mm]		h	α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂ min				
SSA / SSAL 25 T/K	55	30	94	15	85,0	0,640

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952490953
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	60 mm
Diam. extérieur	2.362" inch
Epaisseur	31 mm
Epaisseur	1.22" inch
Type	SA
Poids	640 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE