

Rotule SI

DSSIL6-T-K-DURBAL - DSSIL6-T-K-DURBAL

https://www.123roulement.com/roulement-palier/rotule/si/dssil6-t-k-durbal

DSSIL6-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C1	d1	d2	d3	d4
DSSIL 6 T/K		6	M 6	9	6,75	20	10,0	13	

type	measurement [mm]			α °FS	load rating C ₀ (kg)	weight P ₀ (g)
	l ₁ min	W	h			
DSSI / DSSIL 6 T/K	12	11	30	13	7,7	0,022

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491097
Diam. intérieur	6 mm
Diam. intérieur	0.236" inch
Diam. extérieur	20 mm
Diam. extérieur	0.787" inch
Epaisseur	9 mm
Epaisseur	0.354" inch
Type	SI
Poids	22 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE