

Rotule SI

DSSIL8-T-K-DURBAL - DSSIL8-T-K-DURBAL

https://www.123roulement.com/roulement-palier/rotule/si/dssil8-t-k-durbal

DSSIL8-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]	
right hand thread	left hand thread	d	G
DSSIL 8 T/K		8	M 8
		B	C1
		12	9,00
		d1	d2
		24	12,5
		d3	d4
		16	16

type	measurement [mm]			α °	load rating C ₀ (kg)	weight kg
	l ₁ min	W	h			
DSSIL / DSSIL 8 T/K	16	14	36	14	12,5	0,047

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491165
Diam. intérieur	8 mm
Diam. intérieur	0.315" inch
Diam. extérieur	24 mm
Diam. extérieur	0.945" inch
Epaisseur	12 mm
Epaisseur	0.472" inch
Type	SI
Poids	47 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE