

Rotule SI

SSIL14-T-K-DURBAL - SSIL14-T-K-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/ssil14-t-k-durbal>

SSIL14-T-K



female thread; maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSIL 14 T/K			d	G	B	C1	d1	d2	d3	d4
			14	M 14	19	13,50	36	20,0	25	

type	l1 min	W	h	α	load rating C0 [kN]	weight [kg]
SSI / SSIL 14 T/K	25	22	57	16	31,0	0,160

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491332
Diam. intérieur	14 mm
Diam. extérieur	36 mm
Epaisseur	19 mm
Type	SI
Poids	160 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE