

Rotule SI

SSIL16-T-K-DURBAL - SSIL16-T-K-DURBAL

https://www.123roulement.com/roulement-palier/rotule/si/ssil16-t-k-durbal

SSIL16-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
	SSIL 16 TK	16	M 16	21	15,00	42	22,0	27	

type	measurement [mm]				load rating C ₀ [kN]	weight [g]
	l ₁ min	W	h	α [°]		
SSI / SSIL 16 TK	28	22	64	15	39,0	0,220

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491417
Diam. intérieur	16 mm
Diam. extérieur	42 mm
Epaisseur	21 mm
Type	SI
Poids	220 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE