

Rotule SI

SSIL18-T-K-DURBAL - SSIL18-T-K-DURBAL

https://www.123roulement.com/roulement-palier/rotule/si/ssil18-t-k-durbal

SSIL18-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C1	d1	d2	d3	d4
SSIL 18 T/K		18	M 18 x 1,5	23	16,50	44	25,0	31	

type	measurement [mm]				load rating C ₀ [kg]	weight [g]
	l ₁ min	W	h	α [°]		
SSI / SSIL 18 T/K	32	27	71	15	47,5	0,320

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491493
Diam. intérieur	18 mm
Diam. intérieur	0.709" inch
Diam. extérieur	44 mm
Diam. extérieur	1.732" inch
Epaisseur	23 mm
Epaisseur	0.906" inch
Type	SI
Poids	320 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE