

Rotule SI

SSI30-T-K-DURBAL - SSI30-T-K-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/ssi30-t-k-durbal>

SSI30-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSI 30 T/K			d	G	B	C1	d1	d2	d3	d4
			30	M 30 x 2	37	25,00	70	40,0	50	

type	measurement [mm]			α °	load rating C ₀ (kg)	weight P _{gl}
	l ₁ min	W	h			
SSI / SSI 30 T/K	51	41	110	17	114,0	1,100

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952491691
Diam. intérieur	30 mm
Diam. intérieur	1.181" inch
Diam. extérieur	70 mm
Diam. extérieur	2.756" inch
Epaisseur	37 mm
Epaisseur	1.457" inch
Type	SI
Poids	1100 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE