

## Rotule SI SSIL30-T-K-DURBAL - DSSIL30-T-K-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/dssil30-t-k-durbal>

### SSIL30-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number      |                  | measurement [mm] |          |    |       |    |      |    |    |
|-------------------|------------------|------------------|----------|----|-------|----|------|----|----|
| right hand thread | left hand thread | d                | G        | B  | C1    | d1 | d2   | d3 | d4 |
| SSIL 30 T/K       |                  | 30               | M 30 x 2 | 37 | 25,00 | 70 | 40,0 | 50 |    |

| type              | measurement [mm]   |    |     |          | load rating<br>C <sub>0</sub><br>[kN] | weight<br>[kg] |
|-------------------|--------------------|----|-----|----------|---------------------------------------|----------------|
|                   | l <sub>1</sub> min | W  | h   | α<br>[°] |                                       |                |
| SSI / SSIL 30 T/K | 51                 | 41 | 110 | 17       | 114,0                                 | 1,100          |

## CARACTÉRISTIQUES PRODUIT

|                 |                   |
|-----------------|-------------------|
| Marque          | DURBAL            |
| N° Ean13        | 3663952491721     |
| Diam. intérieur | 30 mm             |
| Diam. extérieur | 70 mm             |
| Epaisseur       | 37 mm             |
| Type            | SI                |
| Poids           | 1100 g            |
| Filetage        | Filetage à gauche |
| Lubrification   | sans              |
| Conditionnement | 1                 |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE