

Rotule SA GAR10-UK-DURBAL - GAR10-UK-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/gar10-uk-durbal>


GAR10-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C1	d2
right hand thread left hand thread GAR 10 UK	10	M 10	9	7,0	29

type	l1, min	l2, min	h	α [°]	load rating C ₀ [kN]	weight (kg)
GAR / GAL 10 UK	26	15	48	12	17,6	0,051

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952492858
Diam. intérieur	10 mm
Diam. extérieur	29 mm
Epaisseur	9 mm
Type	SA
Poids	51 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	-
Norme	Sans norme

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE