

Rotule SA GAR20-UK-2RS-DURBAL - GAR20-UK-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/gar20-uk-2rs-durbal>


GAR20-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	G	B	C ₁	d ₂
right-hand thread GAR 20 UK (-2RS)	20	M 20 x 1,5	16	13,0	53

type	l, min	measurement [mm] l ₁ min	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 20 UK-2RS	43	27	78	9	60,0	0,310

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493060
Diam. intérieur	20 mm
Diam. extérieur	53 mm
Épaisseur	16 mm
Type	SA
Poids	310 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE