

# Rotule GE

## GAR50-UK-2RS-DURBAL - GAR50-UK-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/ge/gar50-uk-2rs-durbal>


### GAR50-UK-2RS



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	G	B	C <sub>1</sub>	d <sub>2</sub>
GAR 50 UK-2RS	50	M 45 x 3	35	30,0	112

type	l <sub>1</sub> min	l <sub>2</sub> min	h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3616060467737
Diam. intérieur	50 mm
Diam. extérieur	112 mm
Epaisseur	35 mm
Type	GE
Poids	3400 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1
Norme	Sans norme

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE