

Rotule GE GAL60-UK-2RS-DURBAL - GAL60-UK-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/ge/gal60-uk-2rs-durbal>


GAL60-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

| order number | d | G | B | C ₁ | d ₂ |
|---------------|----|----------|----|----------------|----------------|
| GAL 60 UK-2RS | 60 | M 52 x 3 | 44 | 38,0 | 135 |

| type | l ₁ min | l ₂ min | h | α [°] | load rating C ₀ [kN] | weight [kg] |
|---------------------|--------------------|--------------------|-----|-------|------------------------------------|----------------|
| GAR / GAL 60 UK-2RS | 115 | 75 | 210 | 6 | 450,0 | 5,900 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3616060467775 |
| Diam. intérieur | 60 mm |
| Diam. extérieur | 135 mm |
| Epaisseur | 44 mm |
| Type | GE |
| Poids | 5900 g |
| Filetage | Filetage à gauche |
| Lubrification | sans |
| Conditionnement | 1 |
| Norme | Sans norme |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE