

Rotule SI

GIL12-UK-DURBAL - GIL12-UK-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/gil12-uk-durbal>

GIL12-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]			
GIL 12 UK	12	M 12	10	C ₁	C ₂	d ₂	d ₄
				8,0	34	17,5	22

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 12 UK	23	50	19	11	24,5	0,096

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493688
Diam. intérieur	12 mm
Diam. extérieur	34 mm
Epaisseur	10 mm
Type	SI
Poids	96 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE