

Rotule SI

GIR15-UK-DURBAL - GIR15-UK-DURBAL

https://www.123roulement.com/roulement-palier/rotule/si/gir15-uk-durbal

GIR15-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]	
GIR 15 UK	d	G
	15	M 14
	B	C ₁
	12	10,0
	d ₂	d ₄
	40	21,0
	26	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIR 15 UK	30	61	22	8	36,0	0,180

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493725
Diam. intérieur	15 mm
Diam. intérieur	0.591" inch
Diam. extérieur	40 mm
Diam. extérieur	1.575" inch
Epaisseur	12 mm
Epaisseur	0.472" inch
Type	SI
Poids	180 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE