

Rotule SI

GIL25-UK-DURBAL - GIL25-UK-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/gil25-uk-durbal>

GIL25-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq 35$ with additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	d	G	B	measurement [mm]			
right hand thread				C ₁	C ₂	d ₂	d ₄
GIL 25 UK	25	M 24 x 2	20	17,0	64	33,5	42

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 25 UK	48	94	36	7	83,0	0,640

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493923
Diam. intérieur	25 mm
Diam. extérieur	64 mm
Epaisseur	20 mm
Type	SI
Poids	640 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE