

# Rotule SI

## GIL25-UK-2RS-DURBAL - GIL25-UK-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/gil25-uk-2rs-durbal>

### GIL25-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE fabric

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
no lubrication necessary,  
maintenance free



order number	d	G	B	C <sub>1</sub>	C <sub>2</sub>	d <sub>2</sub>	d <sub>4</sub>
GIL 25 UK (-2RS)	25	M 24 x 2	20	17,0	64	33,5	42

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GIL 25 UK	48	94	36	7	83,0	0,640

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952493930
Diam. intérieur	25 mm
Diam. extérieur	64 mm
Épaisseur	20 mm
Type	SI
Poids	640 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE