

Rotule SI

GIR30-UK-2RS-DURBAL - GIR30-UK-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/gir30-uk-2rs-durbal>

GIR30-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]		measurement [mm]				load rating		weight
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄	[kg]
GIR 30 UK (-2RS)		30	M 30 x 2	22	19,0	73	40,0	50	
type	measurement [mm]			alpha	load rating	weight			
GIR / GIL 30 UK	t ₃ min	h	W	[°]	C ₀ [kN]	[kg]			
	56	110	41	6	110,0	0,930			

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494012
Diam. intérieur	30 mm
Diam. extérieur	73 mm
Épaisseur	22 mm
Type	SI
Poids	930 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE