

Rotule SI

GIR45-UK-2RS-DURBAL - GIR45-UK-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/gir45-uk-2rs-durbal>

GIR45-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₄	
GIR 45 UK-2RS		45	M 42 x 3	32	27,0	102	58,0	70
type	measurement [mm]			load rating	weight			
	l ₃ min	h	W	C ₀ [kN]	[kg]			
GIR / GIL 45 UK-2RS	65	145	60	7	240,0	2,500		

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494166
Diam. intérieur	45 mm
Diam. intérieur	1.772" inch
Diam. extérieur	102 mm
Diam. extérieur	4.016" inch
Epaisseur	32 mm
Epaisseur	1.26" inch
Type	SI
Poids	2500 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE