


Rotule SI
GIL50-UK-2RS-DURBAL - GIL50-UK-2RS-DURBAL
<https://www.123roulement.com/roulement-palier/rotule/si/gil50-uk-2rs-durbal>

GIL50-UK-2RS

female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 17$ additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary, maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₄	
GIL 50 UK-2RS		50	M 45 x 3	35	30,0	112	62,0 75	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 50 UK-2RS	68	160	65	6	290,0	3,500

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494203
Diam. intérieur	50 mm
Diam. extérieur	112 mm
Epaisseur	35 mm
Type	SI
Poids	3500 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com
03 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE