

Rotule SI

GIR80-UK-2RS-DURBAL - GIR80-UK-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/gir80-uk-2rs-durbal>

GIR80-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]		measurement [mm]			
	d	G	B	C ₁	d ₂	d ₄
GIR 80 UK-2RS	80	M 64 x 4	55	47,0	180	95,0 110

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 80 UK-2RS	85	230	100	6	750,0	12,000

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494326
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	180 mm
Diam. extérieur	7.087" inch
Epaisseur	55 mm
Epaisseur	2.165" inch
Type	SI
Poids	12000 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE