

## Rotule SI PHSL22-DURBAL - PHSL22-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/phsl22-durbal>

### PHSL22



**Description:** DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

**female thread:** lubrication required, according to DIN ISO 12240-4, series K

**Rod end body:** surface chromium plated

**Sliding combination:** steel / heavy duty bronze

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** heavy duty bronze with lubrication

**Lubrication:** lubrication required

| order number | left hand thread | d  | G          | B  | C1    | d1 | d2   | d3 | d4 |
|--------------|------------------|----|------------|----|-------|----|------|----|----|
| PHSL22       |                  | 22 | M 22 x 1,5 | 28 | 20,00 | 54 | 30,0 | 38 |    |

| type          | measurement [mm]   |    |    |       | load rating<br>C <sub>0</sub><br>[kN] | weight<br>[kg] |
|---------------|--------------------|----|----|-------|---------------------------------------|----------------|
|               | I <sub>2</sub> min | W  | h  | α [°] |                                       |                |
| PHS / PHSL 22 | 37                 | 32 | 84 | 15    | 57,0                                  | 0,540          |

## CARACTÉRISTIQUES PRODUIT

|                 |                   |
|-----------------|-------------------|
| Marque          | DURBAL            |
| N° Ean13        | 3663952495415     |
| Diam. intérieur | 22 mm             |
| Diam. extérieur | 54 mm             |
| Epaisseur       | 28 mm             |
| Type            | SI                |
| Poids           | 540 g             |
| Filetage        | Filetage à gauche |
| Lubrification   | sans              |
| Conditionnement | 1                 |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE